

Tubacustik Adhesive

Tubacustik Adhesive is a low thickness acoustic insulation solution in a roll, consisting of two layers of cross-linked polyethylene foam enclosing a floating 99.5% pure single fusion virgin lead foil, with certification and chemical analysis, thickness 0.35 mm.

Tubacustik Adhesive is an acoustic insulation solution for sewage pipes with a sound absorbant function for airborne noise, thanks to a lead foil, and separating function provided by the elasticity of cross-linked polyethylene. To eliminate sound transmission, the product features battened joints that ensures insulation continuity with overlapping lead on lead.

Tubacustik Adhesive has a self-adhesive side to facilitate application onto pipes.

Item specifications

The sound insulation of drain pipes is achieved through the supply and installation of physically cross-linked, closed-cell dry air polyethylene foam, enclosing a 99.5% pure single fusion virgin lead foil, with certification and chemical analysis, total thickness 6 mm; features a selvedge seam for a LEAD on LEAD overlapping and a self-adhesive side.

The material must be accompanied by a certificate of origin.

| | | |
|--------------------------|--------------------------------|------------------|
| <input type="checkbox"/> | Tubacustik Adhesive by Thermak | |
| | m ² | €/m ² |

| SPECIFICATIONS | UM | VALUE |
|---------------------------|-------------------|-------------|
| LENGTH | m | 1.00 x 3.00 |
| WEIGHT | kg/m ² | 4.05 |
| THICKNESS | mm | 6 |
| LEAD SHEET THICKNESS | mm | 0.35 |
| POLYETHYLENE CONDUCTIVITY | W/mK | 0.0348 |
| SOUNDPROOFING CAPACITY | dB | 29 |



THERMAK
info@thermak.it
www.thermak.it

MATCO S.r.l.
Via Quadrelli, 69
37055 Ronco all'Adige (VR) - Italy
Tel. +39.045.6608111